PROPEL ADVANCED PRO 0 DI2

TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Obsidian Pulse
CADRE	Advanced-grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
POIGNÉES	Stratus Lite 2.0
POTENCE	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIGE DE SELLE	Giant Vector, composite, -5/+15mm offset
SELLE	Giant Fleet SL
DÉRAILLEUR	
MANETTES	Shimano Ultegra Di2 ST-R8170
DÉRAILLEUR AVANT	Shimano Ultegra Di2 FD-R8150
DÉRAILLEUR ARRIÈRE	Shimano Ultegra Di2 RD-R8150
FREINS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
LEVIERS DE FREIN	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAÎNE	Shimano Ultegra, CN-M8100
PÉDALIER	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOITIER DE PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
MOYEUX	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
RAYONS	Aero Carbon
PNEUS	CADEX Aero, tubeless, 700x28c (28mm), folding, 240TPI
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 6 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	M/L	L	XL
Longueur de tube de selle (mm)	484	505	528,5	554	576	595
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longueur du tube supérieur (mm)	520	535	550	565	580	600
Longueur du tube de direction (mm)	115	127	145	165	185	200
Angle du tube de direction	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Déport de fourche (mm)	45	45	45	45	45	45
Trail (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Empattement (mm)	971	973	980	990	1006	1020
Longueur des bases (mm)	405	405	405	405	405	405
Drop du boitier de pédalier (mm)	72	72	69,5	69,5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Hauteur en statique (mm)	746	764	787	808	832	847
Largeur de cintre (mm)	380	380	400	400	420	420
Longueur de potence (mm)	80	90	100	110	110	120
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5
Diamètre des roues	700C	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.