

PROPEL ADVANCED PRO 0-DI2

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Abyss Teal/Fluorescent Mint, Obsidian Pulse
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELPEN	Giant Vector, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
AFMONTAGE	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
VOORDERAILLEUR	Shimano Ultegra Di2 FD-R8150
ACHTERDERAILLEUR	Shimano Ultegra Di2 RD-R8150
REMMEN	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
REMHEDELS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x34
AANDRIJVING	Shimano Ultegra, CN-M8100
CRANKSET	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
NAVEN	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
SPAKEN	Aero Carbon
BANDEN	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRA'S	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Adviesprijs: € 6.599,00

GEOMETRIE

FRAME	S	M	M/L	L	XL
Zitbuis Lengte (mm)	505	528,5	554	576	595
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	127	145	165	185	200
Balhoofdbuis Hoek	72,5°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	61,4	58,3	58,3	58,3	58,3
Wielbasis (mm)	973	980	990	1006	1020
Liggende achtervork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67
Stack (mm)	530	546	565	582	596
Reach (mm)	383	388	392	402	412
Stand Over Height (mm)	764	787	808	832	847
Stuur breedte (mm)	380	400	400	420	420
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	165	170	170	172,5	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.