

# PROPEL ADVANCED PRO 0 DI2

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Ocean Twilight/Chrome
<b>FRAME</b>	Advanced-Grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Vector, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Ultegra Di2 ST-R8170
<b>FRONT DERAILLEUR</b>	Shimano Ultegra Di2 FD-R8150
<b>REAR DERAILLEUR</b>	Shimano Ultegra Di2 RD-R8150
<b>BRAKES</b>	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano Ultegra Di2 hydraulic
<b>CASSETTE</b>	Shimano Ultegra, 12-speed, 11x30
<b>CHAIN</b>	Shimano Ultegra, CN-M8100
<b>CRANKSET</b>	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim
<b>TIRES</b>	CADEX Road Race, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	32mm

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8	57.8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.