

PROPEL ADVANCED PRO 0

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Metallic Blue/Carbon, Sangria
CUADRO	Advanced-grade composite, disc
TIJERA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Giant Vector, composite, -5/+15mm offset
ASIENTO	Giant Fleet SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Ultegra Di2 ST-R8170
DESVIADOR	Shimano Ultegra Di2 FD-R8150
CAMBIO TRASERO	Shimano Ultegra Di2 RD-R8150
FRENOS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CADENA	Shimano Ultegra, CN-M8100
MULTIPLICACIÓN	Shimano Ultegra, 36/52, with Giant Power Pro power meterXS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
MAZAS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle,
RAYOS	SAPIM CX-Ray
NEUMÁTICOS	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Precio: \$137,990.00

GEOMETRÍA

CUADRO	S	M	ML	L
Longitud de la Base del Poste de Asiento (mm)	500	520	545	575
Seat Post Insertion Depth (mm)	70	70	70	70
Ángulo de la Base del Poste de Asiento	74.0°	73.5°	73.0°	73.0°
Longitud del Tubo Superior (mm)	535	550	565	580
Longitud del Telescopio (mm)	130	145	165	185
Ángulo del Telescopio	72.3°	73.0°	73.0°	73.0°
Rake (mm)	45	45	45	45
Trail (mm)	62.5	57.8	57.8	57.8
Distancia entre Ejes (mm)	977	980	991	1006
Longitud de Vaina Inferior (mm)	405	405	405	405
Caída del Eje de Centro (mm)	70	70	67	67
Stack (mm)	528	545	562	581
Reach (mm)	383	388	393	402
Altura del Tubo Superior al Suelo (mm)	753	770	794	821
Ancho del Manubrio (mm)	400	420	420	440
Longitud de la Potencia (mm)	90	100	110	110
Longitud de la Biela (mm)	170	172.5	172.5	175
Tamaño de las Ruedas	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.