

# PROPEL ADVANCED PRO 1-AXS

**GIANT**



## SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Cryo Silver
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SLR 1 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GREB / STYRBÅND	Stratus Lite 2.0
FREMPIND	Giant Contact SLR 1 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELPIND	Giant Vector, composite, -5/+15mm offset
SADEL	Giant Fleet SL
GEARGRUPPE	
SKIFTEGREB	SRAM Rival AXS E1
FORSKIFTER	SRAM Rival AXS E1
BAGSKIFTER	SRAM Rival AXS E1
BREMSE	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSEGREB	SRAM Rival AXS E1 hydraulic
KASSETTE	SRAM Rival, 12-speed, 10x36
KÆDE	SRAM Rival E1
KRANKSÆT	SRAM Rival E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
EGER	Sapim CX-Ray
DÆK	Giant Gavia Course 0, tubeless, 700x28c, folding
EKSTRA	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Pris: 41.099,00 kr.

## GEOMETRI

RAMME	S	M	M/L	L	XL
Sadelrørslængde (mm)	505	528,5	554	576	595
Sadelrørsvinkel	74,0°	73,5°	73,0°	73,0°	72,5°
Overrørslængde (mm)	535	550	565	580	600
Kronrørslængde (mm)	127	145	165	185	200
Kronrørsvinkel	72,5°	73,0°	73,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	45	45	45	45	45
Sti (mm)	61,4	58,3	58,3	58,3	58,3
Akselafstand (mm)	973	980	990	1006	1020
Kædestagslængde (mm)	405	405	405	405	405
Krankboks drop (mm)	72	69,5	69,5	67	67
Stack (mm)	530	546	565	582	596
Reach (mm)	383	388	392	402	412
Skridthøjde (mm)	764	787	808	832	847
Styrbredde (mm)	380	400	400	420	420
Frempindslængde (mm)	90	100	110	110	120
Pedalarmslængde (mm)	165	170	170	172,5	172,5
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.