

PROPEL ADVANCED PRO 1-AXS



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | XS, S, M, M/L, L, XL |
| COLOURS | Cryo Silver |
| FRAME | Advanced-grade Composite, 12x142mm thru-axle, UDH compatible, integrated seatpost, disc |
| FORK | Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR Aero 1, one piece bar XS:36/38cm, S:36/38cm, M:37/40cm, M/L:37/40cm, L:39/42cm, XL:39/42cm |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact SLR Aero 1, one piece bar XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| SEATPOST | Giant Vector, composite, -5/+15mm offset |
| SADDLE | Giant Fleet SL |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | SRAM Rival AXS HRD, ED-Rival-E1 |
| FRONT DERAILLEUR | SRAM Rival AXS, FD-Rival-E-E1 |
| REAR DERAILLEUR | SRAM Rival AXS, RD-Rival-E-E1 |
| BRAKES | SRAM Rival AXS HRD, ED-Rival-E1, SRAM PaceLine rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | SRAM Rival AXS HRD, ED-Rival-E1 |
| CASSETTE | SRAM Rival E1 XG-1250, 12-speed, 10-36 |
| CHAIN | SRAM Rival-E1, 12-speed |
| CRANKSET | SRAM Rival E1 DUB, 35/48 with spindle power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WHEELS | |
|---------------------------|--|
| RIMS | Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm |
| HUBS | [F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle |
| SPOKES | Sapim CX-Ray |
| TYRES | Giant Gavia Course 0, tubeless, 700x28c (28mm), folding |
| EXTRAS | Computer mount, water bottle cages, tubeless prepared, 32mm max tyre size |
| LIMITS | |
| MAX TYRE CLEARANCE | 32mm |

Price: \$7,499.00

GEOMETRY

| FRAME | XS | S | M | M/L | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 484 | 505 | 528.5 | 554 | 576 | 595 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 115 | 127 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.5° | 72.5° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 67.8 | 61.4 | 58.3 | 58.3 | 58.3 | 58.3 |
| Wheelbase (mm) | 971 | 973 | 980 | 990 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 72 | 69.5 | 69.5 | 67 | 67 |
| Stack (mm) | 515 | 530 | 546 | 565 | 582 | 596 |
| Reach (mm) | 377 | 383 | 388 | 392 | 402 | 412 |
| Stand Over Height (mm) | 746 | 764 | 787 | 808 | 832 | 847 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172.5 | 172.5 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.