

# PROPEL ADVANCED PRO 1-AXS

GIANT



## TEKNISET TIEDOT

RUNKO	
KOOT	S, M, M/L, L, XL
VÄRIT	Cryo Silver
RUNKO	Advanced-grade Composite, 12x142mm thru-axle, disc
HAARUKKA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SLR 1 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GRIPIT	Stratus Lite 2.0
OHJAINKANNATIN	Giant Contact SLR 1 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATULATOLPPA	Giant Vector, composite, -5/+15mm offset
SATULA	Giant Fleet SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Rival AXS E1
ETUVAIHTAJA	SRAM Rival AXS E1
TAKAVAIHTAJA	SRAM Rival AXS E1
JARRUT	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
JARRUKAHVAT	SRAM Rival AXS E1 hydraulic
RATASPAKKA	SRAM Rival, 12-speed, 10x36
KETJUT	SRAM Rival E1
KAMPISARJA	SRAM Rival E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAVAT	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
PINNAT	Sapim CX-Ray
RENKAAT	Giant Gavia Course 0, tubeless, 700x28c, folding
LISÄTIEDOT	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Suositusinta: 5 549,00 €

## GEOMETRIA

RUNKO	S	M	M/L	L	XL
Satulaputken pituus (mm)	505	528,5	554	576	595
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	72,5°
Vaakaputken pituus (mm)	535	550	565	580	600
Emäputken pituus (mm)	127	145	165	185	200
Emäputken kulma	72,5°	73,0°	73,0°	73,0°	73,0°
Haarukan offset (mm)	45	45	45	45	45
Trail-mitta (mm)	61,4	58,3	58,3	58,3	58,3
Akseliväli (mm)	973	980	990	1006	1020
Takahaarukan alaputken pituus (mm)	405	405	405	405	405
Keskiön pudotus (mm)	72	69,5	69,5	67	67
Stack-mitta (mm)	530	546	565	582	596
Reach-mitta (mm)	383	388	392	402	412
Standover-mitta (mm)	764	787	808	832	847
Ohjaustangon leveys (mm)	380	400	400	420	420
Ohjainkannattimen pituus (mm)	90	100	110	110	120
Kammen pituus (mm)	165	170	170	172,5	172,5
Rengaskoko	700C	700C	700C	700C	700C

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.