

PROPEL ADVANCED PRO 1-AXS

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Cryo Silver
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR 1 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SLR 1 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELPEN	Giant Vector, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
AFMONTAGE	
SHIFTERS	SRAM Rival AXS E1
VOORDERAILLEUR	SRAM Rival AXS E1
ACHTERDERAILLEUR	SRAM Rival AXS E1
REMMEN	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
REMHENDELS	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
AANDRIJVING	SRAM Rival E1
CRANKSET	SRAM Rival E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAVEN	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRA'S	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Adviesprijs: € 5.199,00

GEOMETRIE

FRAME	S	M	M/L	L	XL
Zitbuis lengte (mm)	505	528,5	554	576	595
Zitbuis hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	127	145	165	185	200
Balhoofdbuis Hoek	72,5°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	61,4	58,3	58,3	58,3	58,3
Wielbasis (mm)	973	980	990	1006	1020
Liggende achtervork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67
Stack (mm)	530	546	565	582	596
Reach (mm)	383	388	392	402	412
Stand Over Height (mm)	764	787	808	832	847
Stuur breedte (mm)	380	400	400	420	420
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	165	170	170	172,5	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.