

# PROPEL ADVANCED PRO 1-DI2

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Cryo Silver
<b>FRAME</b>	Advanced-grade Composite, 12x142mm thru-axle, UDH compatible, integrated seatpost, disc
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR Aero 1, one piece bar XS:36/38cm, S:36/38cm, M:37/40cm, M/L:37/40cm, L:39/42cm, XL:39/42cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SLR Aero 1, one piece bar XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Vector, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano 105 Di2 ST-R7170
<b>FRONT DERAILLEUR</b>	Shimano 105 Di2 FD-R7150
<b>REAR DERAILLEUR</b>	Shimano 105 Di2 RD-R7150
<b>BRAKES</b>	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano 105 Di2 hydraulic
<b>CASSETTE</b>	Shimano 105, 12-speed, 11x34
<b>CHAIN</b>	KMC X12
<b>CRANKSET</b>	Shimano 105, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
<b>HUBS</b>	[F] Giant Aero Hub, CenterLock, 12mm thru-axle [R] Giant Aero Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim CX-Ray
<b>TYRES</b>	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
<b>EXTRAS</b>	Computer mount, water bottle cages, tubeless prepared, 32mm max tyre size
LIMITS	
<b>MAX TYRE CLEARANCE</b>	32mm

**Price: \$6,999.00**

## GEOMETRY

FRAME	XS	S	M	M/L	L	XL
Seat Tube Length (mm)	484	505	528.5	554	576	595
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	115	127	145	165	185	200
Head Tube Angle	71.5°	72.5°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	67.8	61.4	58.3	58.3	58.3	58.3
Wheelbase (mm)	971	973	980	990	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69.5	69.5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Stand Over Height (mm)	746	764	787	808	832	847
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5
Wheel Size	700C	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.