

PROPEL ADVANCED PRO 1-DI2

GIANT



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Cryo Silver
QUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	Giant Contact SLR 1 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
PUNHOS	Stratus Lite 2.0
AVANÇO	Giant Contact SLR 1 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ESPIGÃO DE SELIM	Giant Vector, composite, -5/+15mm offset
SELIM	Giant Fleet SL
TRANSMISSÃO	
MANETES	Shimano 105 Di2
DESVIADOR DIANTEIRO	Shimano 105 Di2
DESVIADOR TRASEIRO	Shimano 105 Di2
TRAVÕES	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
MANÍPULOS DOS TRAVÕES	Shimano 105 Di2 hydraulic
CASSETE	Shimano 105, 12-speed, 11x36
CORRENTE	KMC X12L-1
CONJUNTO PEDALEIRO	Shimano 105 with power meter, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
CUBOS	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
RAIOS	Sapim CX-Ray
PNEUS	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Preço: 4 749,00 €

GEOMETRIA

QUADRO	XS	S	M	M/L	L	XL
Comprimento do tubo do assento (mm)	484	505	528,5	554	576	595
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Comprimento do tubo superior (mm)	520	535	550	565	580	600
Comprimento do tubo principal (mm)	115	127	145	165	185	200
Ângulo do tubo principal	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Garfo ancinho (mm)	45	45	45	45	45	45
Trilha (mm)	67,8	61,4	58,3	58,3	58,3	58,3
distância entre eixos (mm)	971	973	980	990	1006	1020
Comprimento Chain Stay (mm)	405	405	405	405	405	405
Suporte inferior (mm)	72	72	69,5	69,5	67	67
Pilha (mm)	515	530	546	565	582	596
Alcançar (mm)	377	383	388	392	402	412
Altura do standover (mm)	746	764	787	808	832	847
Largura do guidão (mm)	380	380	400	400	420	420
Comprimento da haste (mm)	80	90	100	110	110	120
Comprimento da Manivela (mm)	165	165	170	170	172,5	172,5
Tamanho da roda	700C	700C	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.