

PROPEL ADVANCED PRO 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Matte Carbon/Gloss Black
CUADRO	Advanced-grade composite, disc
TIJERA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SL Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Giant Vector, composite, -5/+15mm offset
ASIENTO	Giant Fleet SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Rival eTap AXS
DESVIADOR	SRAM Rival eTap AXS
CAMBIO TRASERO	SRAM Rival eTap AXS
FRENOS	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM Rival eTap AXS hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x30
CADENA	SRAM Rival D1
MULTIPLICACIÓN	SRAM Rival D1 DUB, 35/48 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
MAZAS	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
RAYOS	SAPIM CX-Ray
NEUMÁTICOS	Giant Gavia Course 1, tubeless,700x25c (28mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Precio: \$110,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L
Longitud de la Base del Poste de Asiento (mm)	465	500	520	545	575
Seat Post Insertion Depth (mm)	70	70	70	70	70
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°
Longitud del Tubo Superior (mm)	520	535	550	565	580
Longitud del Telescopio (mm)	120	130	145	165	185
Ángulo del Telescopio	71.0°	72.3°	73.0°	73.0°	73.0°
Rake (mm)	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8
Distancia entre Ejes (mm)	976	977	980	991	1006
Longitud de Vaina Inferior (mm)	405	405	405	405	405
Caída del Eje de Centro (mm)	72	70	70	67	67
Stack (mm)	517	528	545	562	581
Reach (mm)	376	383	388	393	402
Altura del Tubo Superior al Suelo (mm)	722	753	770	794	821
Ancho del Manubrio (mm)	400	400	420	420	440
Longitud de la Potencia (mm)	80	90	100	110	110
Longitud de la Biela (mm)	170	170	172.5	172.5	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.