

# PROPEL ADVANCED PRO 1

GIANT



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Frost Silver
RUNKO	Advanced-Grade Composite, 12x142mm thru-axle, disc
HAARUKKA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ISKUNVAIMENNIN	N/A
KOMONENTIT	
OHJAUSTANKO	Giant Contact SL Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPIT	Stratus Lite 2.0
OHJAINKANNATIN	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATULATOLPPA	Giant Vector, composite, -5/+15mm offset
SATULA	Giant Fleet SL
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Rival eTap AXS
ETUVAIHTAJA	SRAM Rival eTap AXS
TAKAVAIHTAJA	SRAM Rival eTap AXS
JARRUT	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
JARRUKAHVAT	SRAM Rival eTap AXS hydraulic
RATASPAKKA	SRAM Rival, 12-speed, 10x30
KETJUT	SRAM Rival D1
KAMPISARJA	SRAM Rival D1 DUB, 35/48 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAVAT	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Sapim
RENKAAT	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
LISÄTIEDOT	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
RAJOITTEET	
MAX RENGASVARA	32mm

Suositusuhinta: 5 809,00 €

## GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	500	520	545	575	595
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	72,5°
Vaakaputken pituus (mm)	535	550	565	580	600
Emäputken pituus (mm)	130	145	165	185	200
Emäputken kulma	72,3°	73,0°	73,0°	73,0°	73,0°
Haarukan offset (mm)	45	45	45	45	45
Trail-mitta (mm)	62,5	57,8	57,8	57,8	57,8
Akseliväli (mm)	977	980	991	1006	1020
Takahaarukan alaputken pituus (mm)	405	405	405	405	405
Keskiön pudotus (mm)	70	70	67	67	67
Stack-mitta (mm)	528	545	562	581	596
Reach-mitta (mm)	383	388	393	402	412
Standover-mitta (mm)	753	770	794	821	834
Ohjaustangon leveys (mm)	400	420	420	440	440
Ohjainkannattimen pituus (mm)	90	100	110	110	120
Kammen pituus (mm)	170	172,5	172,5	175	175
Rengaskoko	700C	700C	700C	700C	700C

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.