

PROPEL ADVANCED PRO 1



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Midnight Moon
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Vector, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS E1
FRONT DERAILLEUR	SRAM Rival AXS E1
REAR DERAILLEUR	SRAM Rival AXS E1
BRAKES	SRAM Rival AXS E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Rival AXS E1 hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x30
CHAIN	SRAM Rival E1
CRANKSET	SRAM Rival E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.