

# PROPEL ADVANCED PRO 1

GIANT



## SPECS

| RAM          |   |
|--------------|---|
| STORLEKAR    | XS, S, M, M/L, L, XL  |
| FÄRGER       | Frost Silver  |
| RAM          | Advanced-Grade Composite, 12x142mm thru-axle, disc  |
| GAFFEL       | Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc                            |
| BAKDÄMPARE   | N/A   |
| KOMponenter  |   |
| STYRE        | Giant Contact SL Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm  |
| GREPPAR      | Stratus Lite 2.0  |
| STAM         | Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm  |
| SADELSTOLPE  | Giant Vector, composite, -5/+15mm offset  |
| SADEL        | Giant Fleet SL  |
| DRIVLINJA    |   |
| VÄXLAR       | SRAM Rival eTap AXS   |
| FRAMVÄXEL    | SRAM Rival eTap AXS   |
| BAKVÄXEL     | SRAM Rival eTap AXS   |
| BROMSAR      | SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm  |
| BROMSSPAKAR  | SRAM Rival eTap AXS hydraulic   |
| KASSETT      | SRAM Rival, 12-speed, 10x30   |
| KEDJA        | SRAM Rival D1   |
| VEVPARTI     | SRAM Rival D1 DUB, 35/48 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BROMSREGLAGE | SRAM DUB, press fit   |

| HJUL            |  |
|-----------------|--|
| FÄLGAR          | Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm   |
| NAV             | [F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle |
| EKRAR           | Sapim  |
| DÄCK            | Giant Gavia Course 1, tubeless, 700x25c (28mm), folding  |
| EXTRAFUNKTIONER | computer mount, water bottle cages, tubeless prepared, 32mm max tire size  |
| GRÄNSER         |  |
| MAX DÄCKAVSTÅND | 32mm   |

Price: 65 890,00 kr

## GEOMETRY

| RAM                   | S     | M     | ML    | L     | XL    |
|-----------------------|-------|-------|-------|-------|-------|
| Längd sadelrör (mm)   | 500   | 520   | 545   | 575   | 595   |
| Vinkel sadelrör       | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Topprörets längd (mm) | 535   | 550   | 565   | 580   | 600   |
| Styrhuvud Längd (mm)  | 130   | 145   | 165   | 185   | 200   |
| Vinkel styrhuvud      | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Gaffelvinkel (mm)     | 45    | 45    | 45    | 45    | 45    |
| Spår (mm)             | 62,5  | 57,8  | 57,8  | 57,8  | 57,8  |
| Hjulbas (mm)          | 977   | 980   | 991   | 1006  | 1020  |
| Kedjestagslängd (mm)  | 405   | 405   | 405   | 405   | 405   |
| Nedre fäste Drop (mm) | 70    | 70    | 67    | 67    | 67    |
| Stack (mm)            | 528   | 545   | 562   | 581   | 596   |
| Reach (mm)            | 383   | 388   | 393   | 402   | 412   |
| Stå över höjden (mm)  | 753   | 770   | 794   | 821   | 834   |
| Styrets bredd (mm)    | 400   | 420   | 420   | 440   | 440   |
| Stamlängd (mm)        | 90    | 100   | 110   | 110   | 120   |
| Vevlängd (mm)         | 170   | 172,5 | 172,5 | 175   | 175   |
| Hjulstorlek           | 700C  | 700C  | 700C  | 700C  | 700C  |

All specifications listed are subject to change without notice.