

PROPEL ADVANCED PRO-DA



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Supernova Grey
FRAME	Advanced-grade composite, UDH, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Vector, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	Shimano Dura-Ace Di2 ST-R9270
FRONT DERAILLEUR	Shimano Dura-Ace Di2 FD-R9250
REAR DERAILLEUR	Shimano Dura-Ace Di2 RD-R9250
BRAKES	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Dura-Ace Di2
CASSETTE	Shimano Dura Ace, 11x34
CHAIN	Shimano Dura-Ace CN-M9100
CRANKSET	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
SPOKES	Aero Carbon
TYRES	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Price: €7,749.00

GEOMETRY

FRAME	S	M	M/L	L	XL
Seat Tube Length (mm)	505	528.5	554	576	595
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	535	550	565	580	600
Head Tube Length (mm)	127	145	165	185	200
Head Tube Angle	72.5°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	61.4	58.3	58.3	58.3	58.3
Wheelbase (mm)	973	980	990	1006	1020
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67
Stack (mm)	530	546	565	582	596
Reach (mm)	383	388	392	402	412
Stand Over Height (mm)	764	787	808	832	847
Handlebar Width (mm)	380	400	400	420	420
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	165	170	170	172.5	172.5
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.