

PROPEL ADVANCED PRO-DA

GIANT



SPECIFIKACIJE

| OKVIR | |
|---------------------|--|
| VELIKOSTI | XS, S, M, M/L, L, XL |
| BARVE | Supernova Grey |
| OKVIR | Advanced-grade Composite, 12x142mm thru-axle, disc |
| VILICE | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| KOMPONENTE | |
| KRMILO | Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm |
| GRIPS | Stratus Lite 2.0 |
| OPORA KRMILA | Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| OPORA SEDEŽA | Giant Vector, composite, -5/+15mm offset |
| SEDEŽ | Giant Fleet SL |
| POGON | |
| PRESTAVNE ROČICE | Shimano Dura-Ace Di2 ST-R9270 |
| PREDNJI MENJALNIK | Shimano Dura-Ace Di2 FD-R9250 |
| ZADNJI MENJALNIK | Shimano Dura-Ace Di2 RD-R9250 |
| ZAVORE | Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm |
| ZAVORNE ROČICE | Shimano Dura-Ace Di2 |
| VERIGA | Shimano Dura-Ace CN-M9100 |
| GONILKE Z VERIŽNIKI | Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| OBROČNIKI | |
|-----------|--|
| OBROČI | Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm |
| PESTA | [F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle |
| NAPERE | Aero Carbon |
| PLAŠČI | CADEX Aero, tubeless, 700x28c (28mm), folding |
| DODATKI | computer mount, water bottle cages, tubeless prepared, 32mm max tire size |

GEOMETRIJA

| OKVIR | XS | S | M | M/L | L | XL |
|--|-------|-------|-------|-------|-------|-------|
| Dolžina sedežne cevi (mm) | 484 | 505 | 528,5 | 554 | 576 | 595 |
| Kot sedežne cevi | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Višina glave okvirja (mm) | 115 | 127 | 145 | 165 | 185 | 200 |
| Krmilni kot | 71,5° | 72,5° | 73,0° | 73,0° | 73,0° | 73,0° |
| Zamik vpetja osi (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 67,8 | 61,4 | 58,3 | 58,3 | 58,3 | 58,3 |
| Medosna razdalja (mm) | 971 | 973 | 980 | 990 | 1006 | 1020 |
| Dolžina cevi ob verigi (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 72 | 69,5 | 69,5 | 67 | 67 |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 515 | 530 | 546 | 565 | 582 | 596 |
| Doseg (mm) | 377 | 383 | 388 | 392 | 402 | 412 |
| Višina zgornje cevi (mm) | 746 | 764 | 787 | 808 | 832 | 847 |
| Širina krmila (mm) | 380 | 380 | 400 | 400 | 420 | 420 |
| Dolžina opore krmila (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Dolžina gonilke (mm) | 165 | 165 | 170 | 170 | 172,5 | 172,5 |
| Velikost obročnikov | 700C | 700C | 700C | 700C | 700C | 700C |

Vse navedene specifikacije se lahko spremenijo brez obvestila.