

PROPEL ADVANCED PRO DISC FRAMESET





SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Carbon, Deep Lake Concrete
FRAME	Advanced-Grade Composite, disc
FORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
SHOCK	N/A
COMPONENTS	
SEATPOST	Giant Vector, composite, -5/+15mm offset

WHEELS	
EXTRAS	28mm max tire size, 12mm thru-axles

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	500	520	575	595
Seat Tube Angle	73.5°	73.0°	73.0°	72.0°
Top Tube Length (mm)	535	550	580	605
Head Tube Length (mm)	130	145	185	200
Head Tube Angle	72.5°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45
Trail (mm)	60	57	57	57
Wheelbase (mm)	970	976	1007	1021
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	68	68	65	65
Stack (mm)	529	545	581	595
Reach (mm)	378	383	402	412
Stand Over Height (mm)	769	787	829	843
Handlebar Width (mm)	400	420	440	440
Stem Length (mm)	90	100	110	120
Crank Length (mm)	170	172.5	175	175
Wheel Size	700C	700C	700C	700C

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.