

PROPEL ADVANCED PRO FRAMESET



SPECS

FRAME	
SIZES	S, M, M/L, L
COLOURS	Gloss Carbon/Chrome
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc, electronic and mechanical drive train compatible.
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Giant Vector, composite, -5/+15mm offset
DRIVETRAIN	
SHIFTERS	Compatible with Shimano Di2, SRAM AXS/eTap, new Campagnolo Super Record and Shimano 9100, 8000, 7100, 7000 mechanical groupsets.
BOTTOM BRACKET	Press fit 41x86.5mm. Not included

WHEELS

EXTRAS Out front computer mount, water bottle cages

LIMITS

MAX TYRE CLEARANCE 32mm

Price: £2,199.00

GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	500	520	545	575
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	535	550	565	580
Head Tube Length (mm)	130	145	165	185
Head Tube Angle	72.3°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45
Trail (mm)	62.5	57.8	57.8	57.8
Wheelbase (mm)	977	980	991	1006
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67
Stack (mm)	528	545	562	581
Reach (mm)	383	388	393	402
Stand Over Height (mm)	753	770	794	821
Handlebar Width (mm)	400	420	420	440
Stem Length (mm)	90	100	110	110
Crank Length (mm)	170	172.5	172.5	175
Wheel Size	700C	700C	700C	700C

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.