

PROPEL ADVANCED PRO FRAMESET



SPECS

TELAIO	
TAGLIE	XS, S, M, M/L, L, XL
COLORAZIONI	Polar Zone/Chrome, Carbon/Chrome
TELAIO	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORCELLA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTISTICA	
REGGISELLA	Giant Vector, composite, -5/+15mm offset

RUOTE	
EXTRA	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITI	
SEZIONE MASSIMA SUPPORTATA	32mm

Prezzo: 2.599,00 €

GEOMETRIA

TELAIO	XS	S	M	L	XL
Lunghezza Tubo Sella (mm)	465	500	520	575	595
Profondità inserimento reggisella (mm)	70	70	70	70	70
Angolo Tubo Sella	74,5°	74,0°	73,5°	73,0°	72,5°
Lunghezza Tubo Orizzontale (mm)	520	535	550	580	600
Lunghezza Tubo Sterzo (mm)	120	130	145	185	200
Angolo Sterzo	71,0°	72,3°	73,0°	73,0°	73,0°
Rake Forcella (mm)	45	45	45	45	45
Avancorsa (mm)	70,5	62,5	57,8	57,8	57,8
Interasse (mm)	976	977	980	1006	1020
Lunghezza Carro Posteriore (mm)	405	405	405	405	405
Drop Movimento Centrale (mm)	72	70	70	67	67
Stack (mm)	517	528	545	581	596
Reach (mm)	376	383	388	402	412
Altezza stand over (mm)	722	753	770	821	834
Larghezza Manubrio c/c (mm)	400	400	420	440	440
Lunghezza Attacco Manubrio (mm)	80	90	100	110	120
Lunghezza Pedivella (mm)	170	170	172,5	175	175
Dimensione Ruote	700C	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.