

PROPEL ADVANCED SL 0 CAMPAGNOLO



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS,S,M,ML
BARVE	碳纖黑
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm,
OPORA KRMILA	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm
OPORA SEDEŽA	Giant Integrated Seatpost, -5/+15mm offset
SEDEŽ	CADEX AMP 3D
POGON	
PRESTAVNE ROČICE	Super Record 13 Groupset
PREDNJI MENJALNIK	Super Record 13 front derailleur
ZADNJI MENJALNIK	Super Record 13 direct rear derailleur
ZAVORE	Super Record 13 Caliper [F]160mm, [R]140mm Campagnolo Rotor 03 [F]160mm, [R]140mm
ZAVORNE ROČICE	Super Record 13 Ergopower controls
VERIŽNIK	Ultra Titanium Cassette 11-36
VERIGA	Super Record 13 chain
GONILKE Z VERIŽNIKI	Super Record 13 crankset with Power Meter Ultra Carbon chainring 50x34 XS:165mm, S:165mm, M:170mm, M/L:170mm
BOTTOM BRACKET	Ultra BM 陶瓷軸承(USB)

OBROČNIKI	
OBROČI	CADEX Max 50 WheelSystem, [F]50mm, [R]50mm
PESTA	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Super Aero Carbon Spoke
PLAŠČI	CADEX Aero, tubeless, 700x28c (28mm), folding

GEOMETRIJA

OKVIR	XS	S	M	M/L	L	XL
Dolžina sedežne cevi (mm)	680	710	740	770	800	830
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	115	127	145	165	185	200
Krmilni kot	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Medosna razdalja (mm)	971	973	980	990	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69,5	69,5	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	515	530	546	565	582	596
Doseg (mm)	377	383	388	392	402	412
Višina zgornje cevi (mm)	746	764	787	808	832	847
Širina krmila (mm)	380	380	400	400	420	420
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.