

# PROPEL ADVANCED SL 0-DA

GIANT



## ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Prism Pearl
CUADRO	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
HORQUILLA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
PUÑOS	Stratus Lite 2.0
POTENCIA	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA DE SILLÍN	Advanced SL-grade composite, integrated design, -5/+15mm offset
SILLÍN	CADEX AMP
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Dura-Ace Di2 ST-R9270
DESVIADOR	Shimano Dura-Ace Di2 FD-R9250
CAMBIO TRASERO	Shimano Dura-Ace Di2 RD-R9250
FRENOS	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Dura-Ace Di2
CASSETTE	Shimano Dura-Ace, 12-speed, 11x30
CADENA	Shimano Dura-Ace CN-M9100
JGO. PLATOS Y BIELAS	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
CAJA DE PEDALIER	CEMA Ceramic, press fit

RUEDAS	
LLANTAS	CADEX Max 50 WheelSystem, [F]50mm, [R]50mm
BUJES	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
RADIOS	CADEX Super Aero Carbon
CUBIERTAS	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Precio: 11.499,00 €

## GEOMETRÍA

CUADRO	XS	S	M	M/L	L	XL
Longitud del tubo del sillín (mm)	680	710	740	770	800	830
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	115	127	145	165	185	200
Ángulo del tubo de dirección	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Inclinación de la horquilla (mm)	45	45	45	45	45	45
Trail (mm) (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Distancia entre ejes (mm) (mm)	971	973	980	990	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	72	69,5	69,5	67	67
Stack (mm) (mm)	515	530	546	565	582	596
Reach (mm) (mm)	377	383	388	392	402	412
Altura del suelo al tubo (mm) (mm)	746	764	787	808	832	847
Ancho del manillar (mm) (mm)	380	380	400	400	420	420
Longitud de la potencia (mm) (mm)	80	90	100	110	110	120
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5	172,5
Tamaño de ruedas	700C	700C	700C	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.