

PROPEL ADVANCED SL 0 DURA-ACE

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Black Lava/Monogram
CUADRO	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
TIJERA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Advanced SL-grade composite, integrated design, -5/+15mm offset
ASIENTO	CADEX AMP
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Dura-Ace Di2 ST-R9270
DESVIADOR	Shimano Dura-Ace Di2 ST-R9250
CAMBIO TRASERO	Shimano Dura-Ace Di2 ST-R9250
FRENOS	Shimano Dura-Ace Di2 hydraulic, Shimano RT-MT900 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Dura-Ace Di2
CASSETTE	Shimano Dura-Ace, 12-speed, 11x30
CADENA	Shimano Dura-Ace M9100
MULTIPLICACIÓN	Shimano Dura-Ace, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	CADEX 50 Ultra Disc WheelSystem, [F]50mm, [R]50mm
MAZAS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
RAYOS	CADEX Super Aero Carbon Spoke
NEUMÁTICOS	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Precio: \$238,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud de la Base del Poste de Asiento (mm)	680	710	740	770	800	830
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Longitud del Tubo Superior (mm)	520	535	550	565	580	600
Longitud del Telescopio (mm)	120	130	145	165	185	200
Ángulo del Telescopio	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Rake (mm)	45	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8	57.8
Distancia entre Ejes (mm)	976	977	980	991	1006	1020
Longitud de Vaina Inferior (mm)	405	405	405	405	405	405
Caída del Eje de Centro (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Altura del Tubo Superior al Suelo (mm)	734	755	775	794	821	834
Ancho del Manubrio (mm)	400	400	420	420	440	440
Longitud de la Potencia (mm)	80	90	100	110	110	120
Longitud de la Biela (mm)	170	170	172.5	172.5	175	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.