

PROPEL ADVANCED SL 0 (DURA-ACE)

GIANT



SPECIFIKACIJE

| OKVIR               |                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------|
| VELIKOSTI           | XS, S, M, M/L, L, XL                                                                         |
| BARVE               | Arctic Light/Chrome                                                                          |
| OKVIR               | Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc                   |
| VILICE              | Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| KOMPONENTE          |                                                                                              |
| KRMILO              | Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm                    |
| GRIPS               | Stratus Lite 2.0                                                                             |
| OPORA KRMILA        | Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm                |
| OPORA SEDEŽA        | Advanced SL-grade composite, integrated design, -5/+15mm offset                              |
| SEDEŽ               | CADEX AMP                                                                                    |
| POGON               |                                                                                              |
| PRESTAVNE ROČICE    | Shimano Dura-Ace Di2 ST-R9270                                                                |
| PREDNJI MENJALNIK   | Shimano Dura-Ace Di2 ST-R9250                                                                |
| ZADNJI MENJALNIK    | Shimano Dura-Ace Di2 ST-R9250                                                                |
| ZAVORE              | Shimano Dura-Ace Di2 hydraulic, Shimano RT-MT900 rotors [F]160mm, [R]140mm                   |
| ZAVORNE ROČICE      | Shimano Dura-Ace Di2                                                                         |
| VERIŽNIK            | Shimano Dura-Ace, 12-speed, 11x30                                                            |
| VERIGA              | Shimano Dura-Ace M9100                                                                       |
| GONILKE Z VERIŽNIKI | Shimano Dura-Ace, 40/54 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm         |
| BOTTOM BRACKET      | CEMA Ceramic, press fit                                                                      |

| OBROČNIKI          |                                                                                                                              |
|--------------------|------------------------------------------------------------------------------------------------------------------------------|
| OBROČI             | CADEX Ultra 50 WheelSystem, [F]50mm, [R]50mm                                                                                 |
| PESTA              | [F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle |
| NAPERE             | CADEX Super Aero Carbon Spoke                                                                                                |
| PLAŠČI             | CADEX Aero, tubeless, 700x25c (26.5mm), folding                                                                              |
| DODATKI            | computer mount, water bottle cages, tubeless prepared, 32mm max tire size                                                    |
| LIMITS             |                                                                                                                              |
| MAX TIRE CLEARANCE | 32mm                                                                                                                         |

GEOMETRIJA

| OKVIR                                        | XS    | S     | M     | ML    | L     | XL    |
|----------------------------------------------|-------|-------|-------|-------|-------|-------|
| Dolžina sedežne cevi (mm)                    | 680   | 710   | 740   | 770   | 800   | 830   |
| Kot sedežne cevi                             | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm)                         | 520   | 535   | 550   | 565   | 580   | 600   |
| Višina glave okvirja (mm)                    | 120   | 130   | 145   | 165   | 185   | 200   |
| Krmlini kot                                  | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Zamik vpetja osi (mm)                        | 45    | 45    | 45    | 45    | 45    | 45    |
| Trail (mm)                                   | 70,5  | 62,5  | 57,8  | 57,8  | 57,8  | 57,8  |
| Medosna razdalja (mm)                        | 976   | 977   | 980   | 991   | 1006  | 1020  |
| Dolžina cevi ob verigi (mm)                  | 405   | 405   | 405   | 405   | 405   | 405   |
| Bottom Bracket Drop (mm)                     | 72    | 70    | 70    | 67    | 67    | 67    |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 517   | 528   | 545   | 562   | 581   | 596   |
| Doseg (mm)                                   | 376   | 383   | 388   | 393   | 402   | 412   |
| Višina zgornje cevi (mm)                     | 734   | 755   | 775   | 794   | 821   | 834   |
| Širina krmila (mm)                           | 380   | 380   | 400   | 400   | 420   | 420   |
| Dolžina opore krmila (mm)                    | 80    | 90    | 100   | 110   | 110   | 120   |
| Dolžina gonilke (mm)                         | 165   | 165   | 170   | 170   | 172,5 | 172,5 |

Vse navedene specifikacije se lahko spremenijo brez obvestila.