

PROPEL ADVANCED SL 0

GIANT



SPECS

| FRAME | |
|------------------|--|
| SIZES | XS, S, M, M/L, L, XL |
| COLOURS | Black/Moonstone |
| FRAME | Advanced SL-Grade Composite, integrated seatpost, disc |
| FORK | Advanced SL-grade composite, full-composite OverDrive Aero steerer, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact SLR Aero, OverDrive Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| SEATPOST | Advanced SL - grade composite, integrated design, -5/+15mm offset |
| SADDLE | Giant Fleet SLR |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | Shimano Dura-Ace Di2 ST-R9270 |
| FRONT DERAILLEUR | Shimano Dura-Ace Di2 ST-R9250 |
| REAR DERAILLEUR | Shimano Dura-Ace Di2 ST-R9250 |
| BRAKES | Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | Shimano Dura-Ace Di2 |
| CASSETTE | Shimano Dura-Ace, 12-speed, 11x30 |
| CHAIN | Shimano Dura-Ace M9100 |
| CRANKSET | Shimano Dura-Ace, 36/52 with FC-9200P power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|--------|---|
| RIMS | CADEX 50 Ultra Disc WheelSystem |
| HUBS | [F] CADEX R3-C40 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | CADEX Super Aero Carbon Spoke |
| TIRES | CADEX Aero, tubeless, 700x25c (26.5mm), folding |
| EXTRAS | Computer mount, water bottle cages, tubeless prepared, 30mm max tyre size |

Price: \$14,999.00

GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 680 | 710 | 740 | 770 | 800 | 830 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.0° | 72.3° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 70.5 | 62.5 | 57.8 | 57.8 | 57.8 | 57.8 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 734 | 755 | 775 | 794 | 821 | 834 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.