

# PROPEL ADVANCED SL 0 (RED)\*



## SPECS

FRAME	
<b>SIZES</b>	S, M, M/L, L, XL
<b>COLORS</b>	Arctic Light
<b>FRAME</b>	Advanced SL-Grade Composite, integrated seatpost, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR Aero S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SLR Aero S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Advanced SL-Grade composite, integrated design, -5/+15mm offset
<b>SADDLE</b>	CADEX AMP
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM RED AXS HRD, ED-RED-E1
<b>FRONT DERAILLEUR</b>	SRAM RED AXS, FD-RED-E-E1
<b>REAR DERAILLEUR</b>	SRAM RED AXS, RD-RED-E-E1
<b>BRAKES</b>	SRAM RED AXS HRD, ED-RED-E1, SRAM PaceLine X rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	SRAM RED AXS HRD, ED-RED-E1
<b>CASSETTE</b>	SRAM RED XG-1290, 12-speed, 10-33
<b>CHAIN</b>	SRAM RED-E1, 12-speed
<b>CRANKSET</b>	SRAM RED E1, DUB, 37/50 with power meter S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB Ceramic, Press Fit

WHEELS	
<b>RIMS</b>	CADEX 50 Ultra Disc WheelSystem, [F]50mm, [R]50mm
<b>HUBS</b>	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40 Aero Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	CADEX Super Aero Carbon Spoke
<b>TIRES</b>	CADEX Aero, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	Computer mount, water bottle cages, tubeless prepared, 30mm max tyre size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	30 mm

**Price: \$15,999.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8	57.8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	734	755	775	794	821	834
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.