

PROPEL ADVANCED SL 0-RED



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Superspeed Blue
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VOORVORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELPEN	Advanced SL-grade composite, integrated design, -5/+15mm offset
ZADEL	CADEX AMP
AFMONTAGE	
SHIFTERS	SRAM RED AXS HRD, ED-RED-E1
VOORDERAILLEUR	SRAM RED AXS FD-RED-E-E1
ACHTERDERAILLEUR	SRAM RED AXS RD-RED-E-E1
REMMEN	SRAM RED hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
REMHENDELS	SRAM RED AXS HRD, ED-RED-E1
CASSETTE	SRAM RED, 12-speed, 10x33
AANDRIJVING	SRAM RED CN-RED-E1
CRANKSET	SRAM RED PM E1 DUB, 37/50 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WIELSET	
VELGEN	CADEX Max 50 WheelSystem, [F]50mm, [R]50mm
NAVEN	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	CADEX Super Aero Carbon
BANDEN	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRA'S	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Adviesprijs: € 12.499,00

GEOMETRIE

FRAME	S	M	M/L	L	XL
Zitbuis Lengte (mm)	710	740	770	800	830
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	127	145	165	185	200
Balhoofdbuis Hoek	72,5°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	61,4	58,3	58,3	58,3	58,3
Wielbasis (mm)	973	980	990	1006	1020
Liggende achtervork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67
Stack (mm)	530	546	565	582	596
Reach (mm)	383	388	392	402	412
Stand Over Height (mm)	764	787	808	832	847
Stuur breedte (mm)	380	400	400	420	420
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	165	170	170	172,5	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.