

PROPEL ADVANCED SL 0-RED



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Superspeed Blue
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset
SADDLE	CADEX AMP
DRIVETRAIN	
SHIFTERS	SRAM RED AXS HRD, ED-RED-E1
FRONT DERAILLEUR	SRAM RED AXS FD-RED-E-E1
REAR DERAILLEUR	SRAM RED AXS RD-RED-E-E1
BRAKES	SRAM RED hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM RED AXS HRD, ED-RED-E1
CASSETTE	SRAM RED, 12-speed, 10x33
CHAIN	SRAM RED CN-RED-E1
CRANKSET	SRAM RED PM E1 DUB, 37/50 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WHEELS	
RIMS	CADEX Max 50 WheelSystem, [F]50mm, [R]50mm
HUBS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Super Aero Carbon
TIRES	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Suggested Retail Price (CDN): \$16,899.00

FRAME GEOMETRY

FRAME	XS	S	M	M/L	L
Seat Tube Length (mm)	680	710	740	770	800
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	520	535	550	565	580
Head Tube Length (mm)	115	127	145	165	185
Head Tube Angle	71.5°	72.5°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	67.8	61.4	58.3	58.3	58.3
Wheelbase (mm)	971	973	980	990	1006
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69.5	69.5	67
Stack (mm)	515	530	546	565	582
Reach (mm)	377	383	388	392	402
Stand Over Height (mm)	746	764	787	808	832
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	80	90	100	110	110
Crank Length (mm)	165	165	170	170	172.5
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.