

PROPEL ADVANCED SL 0 (RED)

GIANT

SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, M/L, L, XL
BOJE	Arctic Light/Chrome
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
LULA VOLANA	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
CIJEV SJEDALA	Advanced SL-grade composite, integrated design, -5/+15mm offset
SJEDALO	CADEX AMP
POGON	
RUČICE MJENJAČA	SRAM RED AXS HRD, ED-RED-E1
PREDNJI MJENJAČ	SRAM RED AXS FD-RED-E-E1
STRAŽNJI MJENJAČ	SRAM RED AXS RD-RED-E-E1
KOČNICE	SRAM RED hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
RUČICE KOČNICA	SRAM RED AXS HRD, ED-RED-E1
KAZETA	SRAM RED, 12-speed, 10x33
LANAC	SRAM RED CN-RED-E1
POGON	SRAM RED PM E1 DUB, 37/50 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
OSOVINA POGONA (BB)	SRAM DUB ceramic, press fit

KOTAČI	
OBRUČI	CADEX Ultra 50 WheelSystem, [F]50mm, [R]50mm
NABE	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	CADEX Super Aero Carbon Spoke
GUME	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODACI	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dužina cijevi sjedala (mm)	680	710	740	770	800	830
Kut cijevi sjedala	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Dužina gornje cijevi (mm)	520	535	550	565	580	600
Dužina prednje cijevi (mm)	120	130	145	165	185	200
Kut vilice	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zakrivljenost vilice (offset) (mm)	45	45	45	45	45	45
Staza (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Međuosovinski razmak kotača (mm)	976	977	980	991	1006	1020
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405	405	405	405	405
Položaj osovine pogona (mm)	72	70	70	67	67	67
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	517	528	545	562	581	596
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	376	383	388	393	402	412
Prekoračna visina (mm)	734	755	775	794	821	834
Širina volana (mm)	380	380	400	400	420	420
Dužina lule volana (mm)	80	90	100	110	110	120
Dužina poluge pedale (mm)	165	165	170	170	172,5	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.