

PROPEL ADVANCED SL 0 (RED)

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Arctic Light/Chrome
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset
SADDLE	CADEX AMP
DRIVETRAIN	
SHIFTERS	SRAM RED AXS HRD, ED-RED-E1
FRONT DERAILLEUR	SRAM RED AXS FD-RED-E-E1
REAR DERAILLEUR	SRAM RED AXS RD-RED-E-E1
BRAKES	SRAM RED hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM RED AXS HRD, ED-RED-E1
CASSETTE	SRAM RED, 12-speed, 10x33
CHAIN	SRAM RED CN-RED-E1
CRANKSET	SRAM RED PM E1 DUB, 37/50 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WHEELS	
RIMS	CADEX Ultra 50 WheelSystem, [F]50mm, [R]50mm
HUBS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Super Aero Carbon Spoke
TIRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	734	755	775	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.