

PROPEL ADVANCED SL 0 TEAM

GIANT



產品規格

車架	
尺寸	XS,M, M/L
車架	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
前叉	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm
把手帶/套	Stratus Lite 2.0
擊桿	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm,
座桿	Advanced SL-grade composite, integrated design, -5/+15mm offset
坐墊	CADEX AMP
DRIVETRAIN	
變速把手	Shimano Dura-Ace Di2 ST-R9270
前變速器	Shimano Dura-Ace Di2 ST-R9250
後變速器	Shimano Dura-Ace Di2 ST-R9250
煞車系統	Shimano Dura-Ace Di2 hydraulic, Shimano RT-MT900 rotors [F]160mm, [R]140mm
煞車把手	Shimano Dura-Ace Di2
飛輪	Shimano Dura-Ace, 12-speed, 11x34
鍊條	Shimano Dura-Ace M9100
大齒盤	Shimano Dura-Ace, 34/50 with Shimano FC-9200P power meter XS:165mm, S:165mm, M:170mm, M/L:170mm,
BOTTOM BRACKET (B B)	Shimano, press fit

輪組	
輪圈	CADEX Ultra 50 WheelSystem, [F]50mm, [R]50mm
花鼓	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
輻條	CADEX Super Aero Carbon Spoke
外胎	CADEX Aero, tubeless, 700x25c (26.5mm), folding
其他	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Price: NT\$338,000

車架幾何

車架	XS	S	M	ML
座(立)管長 (mm)	680	710	740	770
座(立)管角度	74.5°	74.0°	73.5°	73.0°
上管長度 (mm)	520	535	550	565
頭管長度 (mm)	120	130	145	165
頭管角度	71.0°	72.3°	73.0°	73.0°
前叉 (mm)	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8
前後輪距 (mm)	976	977	980	991
後下叉長度 (mm)	405	405	405	405
五通下降高度 (mm)	72	70	70	67
頭碗至五通高度 (mm)	517	528	545	562
頭碗至五通長度 (mm)	376	383	388	393
上管至地面高度 (mm)	734	755	775	794
把手寬 (mm)	380	380	400	400
龍頭長度 (mm)	80	90	100	110
曲柄長度 (mm)	165	165	170	170

*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。