

PROPEL ADVANCED SL 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Raw Carbon
RAHMEN	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
GABEL	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GRIFFE	Stratus Lite 2.0
VORBAU	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATTELSTÜTZE	Advanced SL-grade composite, integrated design, -5/+15mm offset
SATTEL	Giant Fleet SLR
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 ST-R8170
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSEN	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BREMSHEBEL	Shimano Ultegra Di2 hydraulic
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano Ultegra, CN-M8100
KURBEL	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
NABE	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
SPEICHEN	Aero Carbon
REIFEN	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

GEOMETRIEDATEN

RAHMEN	XS	S	M	M/L	L	XL
Sitzrohrlänge (mm)	680	710	740	770	800	830
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	115	127	145	165	185	200
Steuerrohr-Winkel	71.5°	72.5°	73.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	67.8	61.4	58.3	58.3	58.3	58.3
Radstand (mm)	971	973	980	990	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	72	69.5	69.5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Überstandshöhe (mm)	746	764	787	808	832	847
Lenkerbreite (mm)	380	380	400	400	420	420
Vorbaulänge (mm)	80	90	100	110	110	120
Kurbellänge (mm)	165	165	170	170	172.5	172.5
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.