

PROPEL ADVANCED SL 1

GIANT



SPECS

| FRAME | |
|------------------|--|
| SIZES | S, M, M/L, L |
| COLOURS | Gloss Aurora Noise/Monogram |
| FRAME | Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc |
| FORK | Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR Aero |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact SLR Aero |
| SEATPOST | Advanced SL-grade composite, integrated design, -5/+15mm offset |
| SADDLE | Giant Fleet SLR |
| PEDALS | PEDALS NOT SUPPLIED |
| DRIVETRAIN | |
| SHIFTERS | Shimano Ultegra Di2 ST-R8170 2x12 |
| FRONT DERAILLEUR | Shimano Ultegra Di2 FD-R8150 |
| REAR DERAILLEUR | Shimano Ultegra Di2 RD-R8150 |
| BRAKES | Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | Shimano Ultegra Di2 hydraulic |
| CASSETTE | Shimano Ultegra, 12-speed, 11x30 |
| CHAIN | Shimano Ultegra, CN-M8100 |
| CRANKSET | Shimano Ultegra, 36/52, with Giant Power Pro power meter |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|--------------------|--|
| RIMS | CADEX 50 Disc WheelSystem, [F]50mm, [R]50mm |
| HUBS | [F] CADEX R1 Hub, CenterLock, 12mm thru-axle [R] CADEX R1 low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | CADEX Aero Carbon Spoke |
| TYRES | CADEX Aero, tubeless, 700x25c (26.5mm), folding |
| EXTRAS | Out front computer mount, water bottle cages, factory tubeless set up |
| LIMITS | |
| MAX TIRE CLEARANCE | 32mm |

GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 680 | 710 | 740 | 770 | 800 | 830 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.0° | 72.3° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 70.5 | 62.5 | 57.8 | 57.8 | 57.8 | 57.8 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 734 | 755 | 775 | 794 | 821 | 834 |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 | 440 | 440 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |

All specifications listed are subject to change without notice.