

# PROPEL ADVANCED SL 1

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Ultra Navy/Azure/Chrome
<b>FRAME</b>	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
<b>FORK</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Advanced SL-grade composite, integrated design, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SLR
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Ultegra Di2 ST-R8170
<b>FRONT DERAILLEUR</b>	Shimano Ultegra Di2 FD-R8150
<b>REAR DERAILLEUR</b>	Shimano Ultegra Di2 RD-R8150
<b>BRAKES</b>	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano Ultegra Di2 hydraulic
<b>CASSETTE</b>	Shimano Ultegra, 12-speed, 11x30
<b>CHAIN</b>	Shimano Ultegra, CN-M8100
<b>CRANKSET</b>	Shimano Ultegra, 36/52, with Giant Power Pro power meter, XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim
<b>TYRES</b>	CADEX Aero, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	32mm

**Price: €7,799.00**

## GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	710	740	770	800
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	535	550	565	580
Head Tube Length (mm)	130	145	165	185
Head Tube Angle	72.3°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45
Trail (mm)	62.5	57.8	57.8	57.8
Wheelbase (mm)	977	980	991	1006
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67
Stack (mm)	528	545	562	581
Reach (mm)	383	388	393	402
Stand Over Height (mm)	755	775	794	821
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	90	100	110	110
Crank Length (mm)	165	170	170	172.5

*All specifications listed are subject to change without notice.*