

PROPEL ADVANCED SL 1

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Gloss Black/Gloss Shoreline/Matte Black
CUADRO	Advanced SL-grade composite, integrated seatpost, disc
TIJERA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Advanced SL - grade composite, integrated design, -5/+15mm offset
ASIENTO	Giant Fleet SLR
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Ultegra Di2 ST-R8170
DESVIADOR	Shimano Ultegra Di2 FD-R8150
CAMBIO TRASERO	Shimano Ultegra Di2 RD-R8150
FRENOS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CADENA	Shimano Ultegra, CN-M8100
MULTIPLICACIÓN	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	CADEX 50 Disc WheelSystem, [F]50mm, [R]50mm
MAZAS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
RAYOS	CADEX Super Aero Carbon Spoke
NEUMÁTICOS	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Precio: \$193,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML
Longitud de la Base del Poste de Asiento (mm)	680	710	740	770
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°
Longitud del Tubo Superior (mm)	520	535	550	565
Longitud del Telescopio (mm)	120	130	145	165
Ángulo del Telescopio	71.0°	72.3°	73.0°	73.0°
Rake (mm)	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8
Distancia entre Ejes (mm)	976	977	980	991
Longitud de Vaina Inferior (mm)	405	405	405	405
Caída del Eje de Centro (mm)	72	70	70	67
Stack (mm)	517	528	545	562
Reach (mm)	376	383	388	393
Altura del Tubo Superior al Suelo (mm)	734	755	775	794
Ancho del Manubrio (mm)	400	400	420	420
Longitud de la Potencia (mm)	80	90	100	110
Longitud de la Biela (mm)	170	170	172.5	172.5
Tamaño de las Ruedas	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.