

# PROPEL ADVANCED SL 1

**GIANT**

## SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, M/L, L, XL
BOJE	Ultra Navy/Azure/Chrome
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
VOLAN	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
LULA VOLANA	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
CIJEV SJEDALA	Advanced SL-grade composite, integrated design, -5/+15mm offset
SJEDALO	Giant Fleet SLR
POGON	
RUČICE MJENJAČA	Shimano Ultegra Di2 ST-R8170
PREDNJI MJENJAČ	Shimano Ultegra Di2 FD-R8150
STRAŽNJI MJENJAČ	Shimano Ultegra Di2 RD-R8150
KOČNICE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
RUČICE KOČNICA	Shimano Ultegra Di2 hydraulic
KAZETA	Shimano Ultegra, 12-speed, 11x30
LANAC	Shimano Ultegra, CN-M8100
POGON	Shimano Ultegra, 36/52, with Giant Power Pro power meter, XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
OSOVINA POGONA (BB)	Shimano, press fit

KOTAČI	
OBRUČI	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NABE	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Sapim
GUME	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODACI	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

## GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dužina cijevi sjedala (mm)	680	710	740	770	800	830
Kut cijevi sjedala	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Dužina gornje cijevi (mm)	520	535	550	565	580	600
Dužina prednje cijevi (mm)	120	130	145	165	185	200
Kut vilice	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zakrivljenost vilice (offset) (mm)	45	45	45	45	45	45
Staza (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Međuosovinski razmak kotača (mm)	976	977	980	991	1006	1020
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405	405	405	405	405
Položaj osovine pogona (mm)	72	70	70	67	67	67
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	517	528	545	562	581	596
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	376	383	388	393	402	412
Prekoračna visina (mm)	734	755	775	794	821	834
Širina volana (mm)	380	380	400	400	420	420
Dužina lule volana (mm)	80	90	100	110	110	120
Dužina poluge pedale (mm)	165	165	170	170	172,5	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.