

PROPEL ADVANCED SL 1

GIANT



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Ultra Navy/Azure/Chrome
RAMME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STYRSTEM	Giant Contact SLR Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SETEPINNE	Advanced SL-grade composite, integrated design, -5/+15mm offset
SADEL	Giant Fleet SLR
DRIVVERK	
GIRHENDLER	Shimano Ultegra Di2 ST-R8170
FRONTGIR	Shimano Ultegra Di2 FD-R8150
BAKGIR	Shimano Ultegra Di2 RD-R8150
BREMSE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BREMSEHENDLER	Shimano Ultegra Di2 hydraulic
KASSETT	Shimano Ultegra, 12-speed, 11x30
KJEDE	Shimano Ultegra, CN-M8100
KRANK	Shimano Ultegra, 36/52, with Giant Power Pro power meter, XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
EIKE	Sapim
DEKK	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	734	755	775	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Alle spesifikasjonene kan endres uten varsel.