

PROPEL ADVANCED SL 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Airglow
OKVIR	Advanced SL-Grade Composite, integrated seatpost, disc
VILICE	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact SLR Aero, OverDrive Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Advanced SL-Grade composite, integrated design, -5/+15mm offset
SEDEŽ	Giant Fleet SLR
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Force eTap AXS
PREDNJI MENJALNIK	SRAM Force eTap AXS
ZADNJI MENJALNIK	SRAM Force eTap AXS
ZAVORE	SRAM Force eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	SRAM Force eTap AXS hydraulic
VERIŽNIK	SRAM Force, 12-speed, 10x28
VERIGA	SRAM Force D1
GONILKE Z VERIŽNIKI	SRAM Force D1 DUB, 35/48 with Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	CADEX 50 Disc WheelSystem, [F]50mm, [R]50mm
PESTA	[F] CADEX R1-S30 Low Friction Hub, CenterLock, 12mm thru-axle, [R] CADEX R1-S30 Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Aero Carbon Spoke
PLAŠČI	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODATKI	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	680	710	740	770	800	830
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	734	755	775	794	821	834
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.