

PROPEL ADVANCED SL 1

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Raw Carbon
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICE	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Advanced SL-grade composite, integrated design, -5/+15mm offset
SEDEŽ	Giant Fleet SLR
POGON	
PRESTAVNE ROČICE	Shimano Ultegra Di2 ST-R8170
PREDNJI MENJALNIK	Shimano Ultegra Di2 FD-R8150
ZADNJI MENJALNIK	Shimano Ultegra Di2 RD-R8150
ZAVORE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano Ultegra Di2 hydraulic
VERIŽNIK	Shimano Ultegra, 12-speed, 11x34
VERIGA	Shimano Ultegra, CN-M8100
GONILKE Z VERIŽNIKI	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
PESTA	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
NAPERE	Aero Carbon
PLAŠČI	CADEX Aero, tubeless, 700x28c (28mm), folding
DODATKI	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	M/L	L	XL
Dolžina sedežne cevi (mm)	680	710	740	770	800	830
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	115	127	145	165	185	200
Krmilni kot	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Medosna razdalja (mm)	971	973	980	990	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69,5	69,5	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	515	530	546	565	582	596
Doseg (mm)	377	383	388	392	402	412
Višina zgornje cevi (mm)	746	764	787	808	832	847
Širina krmila (mm)	380	380	400	400	420	420
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.