

PROPEL ADVANCED SL DISC FRAMESET **GIANT**



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Carbon, Hematite
FRAME	Advanced SL-Grade Composite, integrated seatpost, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
SHOCK	N/A
COMPONENTS	
SEATPOST	Advanced SL-Grade composite, integrated design, -5/+15mm offset

WHEELS

EXTRAS 28mm max tire size, 12mm thru-axles

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	790	820
Seat Tube Angle	74,5°	73,5°	73,0°	73,0°	73,0°	72,0°
Top Tube Length (mm)	515	535	550	570	580	605
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,5°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70	60	57	57	57	57
Wheelbase (mm)	972	970	976	997	1007	1021
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	70	68	68	65	65	65
Stack (mm)	517	529	545	562	581	595
Reach (mm)	372	378	383	398	402	412
Stand Over Height (mm)	744	769	787	807	829	843
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.