

PROPEL ADVANCED SL-FF



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Aurora Chameleon, Cyber Sunset
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, UDH compatible, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset
DRIVETRAIN	
BOTTOM BRACKET	BB86 accepts press fit style BB only, bearing set not included

WHEELS	
EXTRAS	Front & rear 12mm thru-axes, 20mm & 45mm ISP clamps, Bottle Cages, 32mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	32mm

Price: \$5,499.00

GEOMETRY

FRAME	XS	S	M	M/L	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	115	127	145	165	185	200
Head Tube Angle	71.5°	72.5°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	67.8	61.4	58.3	58.3	58.3	58.3
Wheelbase (mm)	971	973	980	990	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69.5	69.5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Stand Over Height (mm)	746	764	787	808	832	847
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5
Wheel Size	700C	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.