

PROPEL ADVANCED SL-FF



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Nitro Purple, Aurora Chameleon, Cyber Sunset
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICE	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
OPORA SEDEŽA	Advanced SL-grade composite, integrated design, -5/+15mm offset

OBROČNIKI	
DODATKI	water bottle cages, 32mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	M/L	L	XL
Dolžina sedežne cevi (mm)	680	710	740	770	800	830
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	115	127	145	165	185	200
Krmljni kot	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Medosna razdalja (mm)	971	973	980	990	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69,5	69,5	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	515	530	546	565	582	596
Doseg (mm)	377	383	388	392	402	412
Višina zgornje cevi (mm)	746	764	787	808	832	847
Širina krmila (mm)	380	380	400	400	420	420
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.