

PROPEL ADVANCED SL-FF TEAM



SPECS

FRAME

SIZES XS, S, M, M/L, L, XL

FRAME Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc

FORK Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc

COMPONENTS

SEATPOST Advanced SL-grade composite, integrated design, -5/+15mm offset

WHEELS

EXTRAS water bottle cages, 32mm max tire size

Suggested Retail Price (CDN): \$5,299.00

FRAME GEOMETRY

FRAME	XS	S	M	M/L	L
Seat Tube Length (mm)	680	710	740	770	800
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	520	535	550	565	580
Head Tube Length (mm)	115	127	145	165	185
Head Tube Angle	71.5°	72.5°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	67.8	61.4	58.3	58.3	58.3
Wheelbase (mm)	971	973	980	990	1006
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69.5	69.5	67
Stack (mm)	515	530	546	565	582
Reach (mm)	377	383	388	392	402
Stand Over Height (mm)	746	764	787	808	832
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	80	90	100	110	110
Crank Length (mm)	165	165	170	170	172.5
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.