

PROPEL ADVANCED SL-FF TEAM



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset

WHEELS	
EXTRAS	water bottle cages, 32mm max tire size

Recommended Retail Price: \$5,300.00

GEOMETRY

FRAME	XS	S	M	M/L	L	XL
Seat Tube Length (inch)	26.8	28	29.1	30.3	31.5	32.7
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (inch)	20.5	21.1	21.7	22.2	22.8	23.6
Head Tube Length (inch)	4.5	5	5.7	6.5	7.3	7.9
Head Tube Angle	71.5°	72.5°	73.0°	73.0°	73.0°	73.0°
Fork Rake (inch)	1.8	1.8	1.8	1.8	1.8	1.8
Trail (inch)	2.6	2.4	2.3	2.3	2.3	2.3
Wheelbase (inch)	38.2	38.3	38.6	39	39.6	40.2
Chain Stay Length (inch)	15.9	15.9	15.9	15.9	15.9	15.9
Bottom Bracket Drop (inch)	2.8	2.8	2.7	2.7	2.6	2.6
Stack (inch)	20.3	20.9	21.5	22.2	22.9	23.5
Reach (inch)	14.8	15.1	15.3	15.4	15.8	16.2
Stand Over Height (inch)	29.4	30.1	31	31.8	32.8	33.3
Handlebar Width (inch)	15	15	15.7	15.7	16.5	16.5
Stem Length (inch)	3.1	3.5	3.9	4.3	4.3	4.7
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8	6.8
Wheel Size	700C	700C	700C	700C	700C	700C

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*