

PROPEL ADVANCED SL-FF TEAM





SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
RAHMEN	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
GABEL	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMponenten	
Sattelstütze	Advanced SL-grade composite, integrated design, -5/+15mm offset

LAUFRÄDER	
EXTRAS	water bottle cages, 32mm max tire size

GEOMETRIEDATEN

RAHMEN	XS	S	M	M/L	L	XL
Sitzrohlrlänge (mm)	680	710	740	770	800	830
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	115	127	145	165	185	200
Steuerrohr-Winkel	71.5°	72.5°	73.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	67.8	61.4	58.3	58.3	58.3	58.3
Radstand (mm)	971	973	980	990	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	72	69.5	69.5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Überstandshöhe (mm)	746	764	787	808	832	847
Lenkerbreite (mm)	380	380	400	400	420	420
Vorbaulänge (mm)	80	90	100	110	110	120
Kurbellänge (mm)	165	165	170	170	172.5	172.5
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.