

PROPEL ADVANCED SL FRAMESET



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Kintsugi Blue/Chrome, Howlite
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axe, disc
COMPONENTS	
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset
DRIVETRAIN	
BOTTOM BRACKET	BB86 accepts press fit style BB only, bearing set not included

WHEELS	
EXTRAS	Front & rear 12mm thru-axes, 20mm & 45mm ISP clamps, Computer Mount, Bottle Cages, 30mm max tyre size
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: \$5,499.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	710	740	770	800	830
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	535	550	565	580	600
Head Tube Length (mm)	130	145	165	185	200
Head Tube Angle	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	62.5	57.8	57.8	57.8	57.8
Wheelbase (mm)	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	755	775	794	821	834
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.