

PROPEL ADVANCED SL FRAMESET

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Kintsugi Blue/Chrome
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset

WHEELS	
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TYRE CLEARANCE	32mm

Price: £3,799.00

GEOMETRY

FRAME	S	M	ML	L
Seat Tube Length (mm)	710	740	770	800
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	535	550	565	580
Head Tube Length (mm)	130	145	165	185
Head Tube Angle	72.3°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45
Trail (mm)	62.5	57.8	57.8	57.8
Wheelbase (mm)	977	980	991	1006
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67
Stack (mm)	528	545	562	581
Reach (mm)	383	388	393	402
Stand Over Height (mm)	755	775	794	821
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	90	100	110	110
Crank Length (mm)	165	170	170	172.5

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.