

# PROPEL ADVANCED SL FRAMESET

**GIANT**



## ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Kintsugi Blue/Chrome
CUADRO	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
HORQUILLA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
TIJA DE SILLÍN	Advanced SL-grade composite, integrated design, -5/+15mm offset

RUEDAS	
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	32mm

**Precio: 3.999,00 €**

## GEOMETRÍA

CUADRO	XS	S	M	ML	L
Longitud del tubo del sillín (mm)	680	710	740	770	800
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580
Longitud del tubo de dirección (mm) (mm)	120	130	145	165	185
Ángulo del tubo de dirección	71,0°	72,3°	73,0°	73,0°	73,0°
Inclinación de la horquilla (mm)	45	45	45	45	45
Trail (mm) (mm)	70,5	62,5	57,8	57,8	57,8
Distancia entre ejes (mm) (mm)	976	977	980	991	1006
Longitud de la vaina (mm) (mm)	405	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	70	70	67	67
Stack (mm) (mm)	517	528	545	562	581
Reach (mm) (mm)	376	383	388	393	402
Altura del suelo al tubo (mm) (mm)	734	755	775	794	821
Ancho del manillar (mm) (mm)	380	380	400	400	420
Longitud de la potencia (mm) (mm)	80	90	100	110	110
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5

*Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.*