

PROPEL ADVANCED SL FRAMESET



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Cosmic Dust
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VOORVORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
ZADELPE	Advanced SL-grade composite, integrated design, -5/+15mm offset

WIELSET	
EXTRA'S	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	32mm

Adviesprijs: € 3.899,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	710	740	770	800	830
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	130	145	165	185	200
Balhoofdbuis Hoek	72,3°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	62,5	57,8	57,8	57,8	57,8
Wielbasis (mm)	977	980	991	1006	1020
Liggende achtervork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	755	775	794	821	834
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.