

PROPEL ADVANCED SL FRAMESET

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Kintsugi Blue/Chrome
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Advanced SL-grade composite, integrated design, -5/+15mm offset

WHEELS	
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8	57.8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	734	755	775	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

All specifications listed are subject to change without notice.