

PROPEL ADVANCED SL TEAM FRAMESET **GIANT**



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, M/L, L, XL
ΣΚΕΛΕΤΟΣ	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
ΠΙΠΟΥΝΙ	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ΕΞΑΡΤΗΜΑΤΑ	
ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ	Advanced SL-grade composite, integrated design, -5/+15mm offset

WHEELS	
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	734	755	775	794	821	834
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση